

Corner established in 1820 by Wm. Laughlin with a post as the monument with witness: 50" white oak N 42 E 8 links, and 12" beech N 86 W 18 links per Marion County Atlas pg. 5. In survey dated January 1857 Mayhew and case report a stone set with witness: 10" swamp ash S 77 ½ E, 43 ½ links and 18" pin oak S 25 W 62 ½ links per Perry Township Legal Survey Book pg. 34. Templeton's Second subdivision plat PB 25, pg. 89-90 by George Schmidt dated April 1935 calls for the corner but no monument described. This subdivision was later vacated. A 1947 subdivision plat by H. Bloemker refers to the corner but does not identify a monument. Original pipes found at the corners of Banta Southwood Addition First Section PB 27, pg. 239, were used to verify the corner location. Location was excavated but no stone was recovered. A survey marker nail was set for the corner monument August 1, 2005.

11001200		
REF.	DISTANCE	DESCRIPTION
1	132.00'	Due N to W Q 7-14-4 Harrison
2.	102.56	Mag nail w/bw SF PwP#403-758 3"up
3.	69.19	NW corner of concrete wall @ gate: Southport Football field/track
4.	110.31	Mag nail w/bw F pwP#89-757 3"up
5.	62.00'	Mag nail w/bw SW PwP#90-757 4"up
-		